

# FP-3000



## ■ FP-3000

**Product Code: 10150**

Product Description: **FirePro Fire Extinguishing Generator FP-3000.**

Features:

- UL, KIWA, BSI, ActivFire Approved
- Carbon-Steel casing Red-coated

## ■ FP-3000S

**Product Code: 10393**

Product Description: **FirePro Fire Extinguishing Generator FP-3000S.**

Features:

- UL, KIWA, BSI, ActivFire Approved
- Stainless steel casing

## ■ FP-3000T

**Product Code: 10318**

Product Description: **FirePro Fire Extinguishing Generator FP-3000T.**

Features:

- Under Process to be UL, KIWA, BSI, ActivFire Approved
- This model can be activated by a Bulb Thermal Activator.
- Carbon-Steel casing Red-coated

## ■ FP-3000TS

**Product Code: 10624**

Product Description: **FirePro Fire Extinguishing Generator FP-3000TS.**

Features:

- Under Process to be UL, KIWA, BSI, ActivFire Approved
- This model can be activated by a Bulb Thermal Activator
- Stainless steel casing

## TECHNICAL INFORMATION

<b>Model</b>	FP-3000 / FP-3000S / FP-3000T / FP-3000TS
<b>Activation mechanism</b>	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
<b>Activator type</b>	Heating element with 2.3 ohm resistance
<b>Current intensity to be tested</b>	Maximum 5 mA
<b>Weight (gross)</b>	16300 g (excluding bracket)
<b>Mass of FPC compound</b>	3000 g
<b>Operational discharge time</b>	15 - 20 seconds
<b>Discharge length</b>	4 m
<b>Dimensions</b>	300 mm x 300 mm x 185 mm
<b>Fire class</b>	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets