
FP-5700



FP-5700

Product Code: 10151

Product Description:

- FirePro Fire Extinguishing Generator FP-5700

Features:

- LPCB, UL, KIWA, MED & BSI Certified
- Carbon steel, red-coated casing

FP-5700T

Product Code: 10318

Product Description:

- FirePro Fire Extinguishing Generator FP-5700T

Features:

- LPCB, UL, KIWA &BSI Approved
- This model can be activated thermally (optional)
- Carbon steel, red-coated casing

FP-5700S

Product Code: 10394

Product Description:

- FirePro Fire Extinguishing Generator FP-5700S

Features:

- LPCB, UL, KIWA, MED & BSI Certified
- Stainless steel casing

FP-5700TS

Product Code: 10625

Product Description:

- FirePro Fire Extinguishing Generator FP-5700TS

Features:

- LPCB, UL, KIWA & BSI Approve
- This model can be activated thermally (optional)
- Stainless steel casing

TECHNICAL INFORMATION

Model	FP-5700 / FP-5700S / FP-5700T / FP-5700TS
Activation method	• Electrical • Thermal (optional for FP-5700T/FP5700TS)
Weight (gross)	26,400 g (excluding bracket)
Mass of FPC compound	5,700 g
Operational discharge time	15 - 20 seconds
Dimensions	300 mm x 300 mm x 300 mm
Fire class	EN 2: A, B, C, F - NFPA 10: A, B, C

Generators are provided complete with brackets